

## 5th Gen. Toyota Rav-4 ALUMINUM



First, remove clip and screw from bracket as shown in Photo 1 and set aside. Next, clean the area where the bracket will be installed (See photo 7 below).

Photo 1



With rear door open, slide top bracket from side as shown in Photos 2 & 3.

Hook top bracket on spoiler as shown in photo 3.

Photo 2

Photo 3





Position top bracket with screw hole aligned with center of hinge as shown in photo 4.

Photo 4



While holding top bracket tight against spoiler as shown in photo 5, <u>carefully</u> close rear door to prevent bracket from scratching your vehicle!

Photo 5



Next, Remove 3MM red film.

Photo 6



Making sure Bracket is hooked tight against rear spoiler and sitting all the way back! Place top bracket's left side parallel with inner roof gutter and press down firmly as shown in Photo 7. (Correct placement is crucial for centering the screw with the door hinge on the under side, also to keep bracket from damaging your cars roof - SEE PHOTO 4.)

Photo 7

Now, open rear door. Reattach clip & screw (set aside earlier), make sure not to cross-thread the screw when attaching as shown in photos 8 & 9.



Photo 8 Photo 9





Close rear door and hook ladder to top bracket in the provided slots as shown in photo 10.

Photo 10



Last, with rear door slightly open, align bottom of the ladder parallel to the bottom of rear hatch door, Attach bottom bracket, with provided screws, to base of the ladder (over the lip of the bottom door hatch) as shown in photo 11. Tighten the ladder screws snug but not fully tightened. Now tighten the bracket set screws until fully tightened. Then, go back and fully tighten ladder screws.

Photo 11

Notice of Disclaimer: NASHFABCO, including its owner and entities are not liable for any damages to vehicle that may occur while installing, nor for any physical injuries sustained during installation or use of product.